STA. 954+70 STA. 954+70 STA. 955+20 STA. 955+20.11

30' RT. 30' RT. 30' RT. 30' RT.

613,934,2444 2 613,891,0298 3 613,931,0711 2 613,868,0849 3 613,855,9424 3 613,853,2937 2

2,090,173,2629 2,090,145,5465 2,090,221,5902 2,090,191,0490 2,090,191,0953 2,090,221,6574 2,090,222,0594

IRON PIN SET INSIDE CONSTRUCTION LIMITS

€ OF PROP. R/W S.R. 37

PROJECT COORDINATES SEE SURVEY CERTIFICATION

MONUMENTS
TO BE SET
DURING
CONSTRUCTION

EXPECTED TO BE DISTURBED

MONUM

ENT

TABLE

OFFSET

NORTHING (Y)

EASTING (X)

REF. MON.

R/W MON.

DESCRIPTION

V 15

SECTION 14 SECTION 23

BA 818 FOR BEARINGS.

ALL BEARINGS SHOWN ARE BASED ON THE OHIO STATE PLANE COORDINATES SYSTEM, SOUTH ZONE.

NOTE: WERE DETERMINED USING DOCUMENTATION ON FILE FROM THE OHIO DEPARTMENT OF TRANSPORTATION, DISTRICT 5 OFFICE, JACKSONTOWN, OHIO. THE EXISTING R/W WIDTH AND LOCATION

PERRY COUNTY ENGINEER CTM APPROVED FOR TRANSFER DATE: 7-10-19

0

0

SECTION BEARFIELD PERRY PART COUNTY TOWNSHIP T13N. R14W

P.I. Sto. 950+59.64 \[ \Delta = 33\cdot 41'\ 00''' (LT) \]
\[ \Delta = 3\cdot 00''\ 00''' \]
\[ P = 1,909.90' \]
\[ T = 578.15' \]
\[ L = 1,122.80' \]
\[ E = 85.59' \] E SURVEY & CONSTRUCTION TATMANS RD. E SURVEY & CONSTRUCTION, S.R. 13 P.I. Sto. 958+27.14 \[ \Delta = 34\cdot 34\cdot 00\cdot (LT) \]
\[ \Delta = 7\cdot 25\cdot 59\cdot \]
\[ R = 716.22\cdot 59\cdot \]
\[ I = 222.85\cdot \]
\[ L = 432.10\cdot \]
\[ E = 33.87\cdot \] SECTION SECTION 15 S 03°13′29″ W 2,246.99′ SECTION 14 N 78°55'02" E STA. 960+08.98

STA. 954+34.23 S.R. 37 = STA. 0+00 TATMANS RD.

COMMENCEMENT POINT
AT LARGE OAK TREE AT THE
NORTHEAST CORNER OF
SOUTHEAST CUARTER OF
SECTION 15, AS REFERENCED
IN A 2.57 ACRE SURVEY BY KEVIN CANNON,
PS 7224, JUNE 2002
STA. 939+81.57
1,948.53' LT.

000

I, Charles W. Price, Jr., P. S. have conducted a survey of the existing conditions for the Ohio Department of Transportation in December, 2012. The results of that survey are contained herein.

system, NAD 83, South Zone.

The horizontal coordinates expressed herein are based on the Ohio State Plane Coordinates

centerline of existing Right of Way for property takes contained herein. As a part of this project I have reestablished the locations of the existing property lines and

Take, present roadway occupied (PRO), Net Take and Net Residue; as well as prepared descriptions necessary to acquire the parcels as shown herein. As a part of this project I have established the proposed property lines, calculated the the legal

As a part of this work I have set shown herein. monuments at the proposed property corners, and other points

4733-37 commonly known as "A Minimum Standards for Boundary Surveys in the State of All of my work contained herein was conducted in accordance with Ohio Administrative Code Ohio" unless so noted. The iron pins and caps will be 3/4" x 30" rebar with aluminum cap stamped "Odot R/W District 5".

The words I and my as used herein are to mean direct supervision. that either myself

Date: 21/02/12

IRON PIN FOUND W/ ID CAP
IRON PIN SET W/ ID CAP
IRON PIPE FOUND

CENTERLINE PLAT WITH THE NEW LOCATIONS SHALL BE RECORDED IN THE

RECORDED RECEIVED

2019 2019

Charles

ADMINISTRATOR OF THE OHIO DEPARTMENT OF TRANSPORTATION. A REVISED

THIS PLAT, REQUIRES PRIOR APPROVAL OF THE DISTRICT REAL ESTATE

RIGHT OF WAY MONUMENTS ARE SHOWN ON STANDARD CONSTRUCTION DRAWING SPECIFICATIONS FOR CENTERLINE MONUMENTS, REFERENCE MONUMENTS AND APPLICABLE COUNTY RECORDS AND THE OHIO DEPARTMENT OF TRANSPORTATION.

TRANSPORTATION.

RM-1.1 OF THE OHIO DEPARTMENT OF

P.K. NAIL FOUND P.K. NAIL SET

IRON PIPE SET

RAILROAD SPIKE SET

RAILROAD SPIKE FOUND

IRON PIN FOUND

PROPOSED CONCRETE MONUMENT

THE IRON PIN WITH CAP (WHEN REQUIRED) ARE TO BE SET BY THE CONTRACTOR'S SURVEYOR.

CHANGES OR ALTERATIONS TO THE LOCATION OF ANY MONUMENTS SHOWN ON

PROPOSED R/W MONUMENT BOX EXISTING CONCRETE STONE FOUND EXISTING R/W MONUMENT BOX

AT THE TIME OF CONSTRUCTION.

BOXIS) AND REFERENCE MONUMENTS WILL BE INSTALLED BY THE HIGHWAY CONTRACTOR PLACEMENT OF ALL MONUMENTS SHALL BE UNDER THE DIRECTION OF A SURVEYOR REGISTERED IN THE STATE OF OHIO. THE CENTERLINE MONUMENT ASSEMBLY THE PROPOSED RIGHT OF WAY SHALL BE REFERENCED FROM THE CENTERLINE OF RIGHT OF WAY.

ENT LEGEND

EXISTING CONCRETE MONUMENT



PER-37-18.09

CENTERLINE PLAT

201900002598
Filed for Record in
Filed for Record in
PERRY COUNTY, OHIO
JACKIE HOOVER, RECORDER
07-18-2019 At 01:36 pm.
43.20 C.S C.P.

PID NO. 91851 HORIZONTAL SCALE IN FEE

