

SECTIONS 21 & 22, T16N, R16W,
READING TOWNSHIP
PERRY COUNTY

S 86°35'52" E 2,673.40'

NORTHEAST CORNER
SECTION 21
NORTHWEST CORNER
SECTION 22

SECTION 16
SECTION 21

SECTION 16
SECTION 15

SECTION 15
SECTION 22

N 04°16'49" E 2,693.17'
HALF SECTION LINE

APPROVED FOR
TRANSFER
BY: CTM DATE: 7-10-19
PERRY COUNTY ENGINEER

MONUMENT TABLE

£ OF PROP. R/W S.R. 668	PROJECT COORDINATES SEE SURVEY CERTIFICATION	MONUMENTS TO BE SET DURING CONSTRUCTION	R/W MON. EXPECTED TO BE DISTURBED	DESCRIPTION
STATION	OFFSET	NORTHING (Y)	EASTING (X)	CENTERLINE REF. MON.
STA. 797+50	40' LT.	648,668.4735	2,024,074.3973	1
STA. 797+50	35' RT.	648,662.8176	2,024,149.1838	1
STA. 800+00	30' LT.	648,917.0075	2,024,103.2217	1
STA. 800+00	30' RT.	648,912.4828	2,024,183.0509	1
TOTAL TO GENERAL SUMMARY				4
				0

MONUMENT LEGEND

- EXISTING CONCRETE STONE FOUND
- EXISTING R/W MONUMENT BOX
- PROPOSED R/W MONUMENT BOX
- EXISTING CONCRETE MONUMENT
- PROPOSED CONCRETE MONUMENT
- RAILROAD SPIKE FOUND
- RAILROAD SPIKE SET
- IRON PIN FOUND
- IRON PIN FOUND W/ ID CAP
- IRON PIN SET W/ ID CAP
- IRON PIPE FOUND
- IRON PIPE SET
- P.K. NAIL FOUND
- P.K. NAIL SET

THE PROPOSED RIGHT OF WAY SHALL BE REFERENCED FROM THE CENTERLINE
OF RIGHT OF WAY.

PLACEMENT OF ALL MONUMENTS SHALL BE UNDER THE DIRECTION OF A SURVEYOR
REGISTERED IN THE STATE OF OHIO. THE CENTERLINE REFERENCE MONUMENTS WILL
BE INSTALLED BY THE HIGHWAY CONTRACTOR AT THE TIME OF CONSTRUCTION.

THE IRON PIN WITH CAP (WHEN REQUIRED) ARE TO BE SET BY THE CONTRACTOR'S
SURVEYOR.

CHANGES OR ALTERATIONS TO THE LOCATION OF ANY MONUMENTS SHOWN ON
THIS PLAT, REQUIRES PRIOR APPROVAL OF THE DISTRICT REAL ESTATE
ADMINISTRATOR OF THE OHIO DEPARTMENT OF TRANSPORTATION. A REVISED
CENTERLINE PLAT WITH THE NEW LOCATIONS SHALL BE RECORDED IN THE
APPLICABLE COUNTY RECORDS AND THE OHIO DEPARTMENT OF TRANSPORTATION.
SPECIFICATIONS FOR CENTERLINE MONUMENTS, REFERENCE MONUMENTS AND
RIGHT OF WAY MONUMENTS ARE SHOWN ON STANDARD CONSTRUCTION DRAWING
RM-1.1 OF THE OHIO DEPARTMENT OF TRANSPORTATION.

£ SURVEY & CONSTRUCTION, S.R. 668

END PROJECT
STA. 798+70.17
S.R. 668

BEGIN PROJECT
STA. 798+23.83
S.R. 668

Plat Book
6 pg 5
Sheet 467

201900002599
Filed for Record in
PERRY COUNTY, OHIO
JACKIE HOOVER, RECORDER
07-18-2019 At 01:36 pm.
PLAT SMALL
43.20

BASIS FOR BEARINGS.

ALL BEARINGS SHOWN ARE BASED ON THE OHIO STATE PLANE
COORDINATES SYSTEM, GRID COORDINATES, SOUTH ZONE, NAD 1983
(CONUS) GEOID 12A (OHIO).

NOTE: THE EXISTING R/W WIDTH AND LOCATION
WERE DETERMINED USING DOCUMENTATION ON FILE
FROM THE OHIO DEPARTMENT OF TRANSPORTATION,
DISTRICT 5 OFFICE, JACKSONTOWN, OHIO.

I, Charles W. Price, Jr., P. S. have conducted a survey of the existing conditions for the Ohio
Department of Transportation in November, 2013. The results of that survey are contained herein.
The horizontal coordinates expressed herein are based on the Ohio State Plane Coordinates
system, Grid coordinates, South Zone, NAD 1983 (Conus) Geoid G12A (Ohio).
As a part of this project I have reestablished the locations of the existing property lines and
centerline of existing Right of Way for property takes contained herein.

As a part of this project I have established the proposed property lines, calculated the Cross
Take, present roadway occupied (PRO), Net Take and Net Residue; as well as prepared the legal
descriptions necessary to acquire the parcels as shown herein.


As a part of this work I have set monuments at the proposed property corners, and other points
shown herein.

The iron pins and caps will be 3/4" x 30" rebar with aluminum cap stamped "Odor R/W District 5".
All of my work contained herein was conducted in accordance with Ohio Administrative Code
4133-37 commonly known as "Minimum Standards for Boundary Surveys in the State of
Ohio" unless so noted.

The words I and my as used herein are to mean that either myself or someone who I employ may
direct supervision.

Charles W. Price, Jr., Professional Land Surveyor # 7825

Date: 10/30/14



0 100 200
HORIZONTAL
SCALE IN FEET

PID NO.
93257

R/W DESIGNER
C.S.
R/W REVIEWER
C.P.

CENTERLINE PLAT

PER-668-15.12

2 / 4
30
32